



INSULATION MACHINE CORP

Accu1 9218 CE

Insulation Blowing Machine



Rugged, powerful and portable, the Accu1 9218 CE all-fiber blowing machine can be used for both loose fill and spray-on applications. Designed for versatility and economical operation with the professional contractor in mind. The Accu1 9218 CE is constructed with standardized parts and has the best production of all a 230V, CE compliant machines.

Production Rates

Cellulose: 1350 lbs/hr.
Fiberglass: 300 lbs/hr.
Rockwool: 450 lbs/hr.

Specifications

- Weight: 175 lbs.
- Dimensions: 20"W x 24"D x 48"H
- Airlock: 18" long x 6" diameter
- Blower Sizes: 5.5 amp/2-stage (standard) (6.8 amp/ 3 stage available)
- Hopper capacity: 8 cu.ft.
- Power requirements: Single input 20 amp/240V 50hz
- Hose: 2.5" diameter up to 200 feet
- Remote and 100' remote cord standard

Features

- Modular component design
- Welded steel construction with powder coated finish
- Hopper guards
- 1 hp TEFC drive motor
- Agitator/shredder system
- Recessed control panel
- Limited moving parts

Benefits

- Quick repairs and maintenance
- Resists damage and corrosion
- Operator safety
- Processes the toughest blowing materials
- Allows for greater conditioning of fibers
- Avoids unintended power shut downs
- Reduces frequency of breakdowns and down time